




Projet / Type \_\_\_\_\_

Notes \_\_\_\_\_

Quantité / Date \_\_\_\_\_



**Général**

Plafond / mur , Rail \_\_\_\_\_

rotation 360° \_\_\_\_\_

noir , RAL9005 <sup>1</sup> \_\_\_\_\_

1980 lm/m \_\_\_\_\_

IP20 \_\_\_\_\_

3570 lm \_\_\_\_\_

**LED**

2700 K \_\_\_\_\_

CRI ≥ 80 \_\_\_\_\_

L80 / 50000 h \_\_\_\_\_

sécurité photobio. RG 0 - aucun risque \_\_\_\_\_

MacAdam initial ≤ 3 SDCM \_\_\_\_\_

MR 0.47 \_\_\_\_\_

MDER 0.42 \_\_\_\_\_

**Electrique**

DALI-2 \_\_\_\_\_

32 W \_\_\_\_\_

CP3 48V \_\_\_\_\_

112 lm/W \_\_\_\_\_

1 DALI Addr. \_\_\_\_\_

18 W/m \_\_\_\_\_

**Physique**

longueur 1810 mm \_\_\_\_\_


largeur 33 mm \_\_\_\_\_

hauteur 33 mm \_\_\_\_\_


0.6 kg \_\_\_\_\_

<sup>1</sup> Code RAL

**Répartition de la lumière**



**Dessin de fabrication**



**Notice de montage**

