

# TULA nano suspended

canopy surface

049-5710418M 005-2602138



Projet / Type \_\_\_\_\_

Notes \_\_\_\_\_

Quantité / Date \_\_\_\_\_



## Général

Plafond , Suspendu \_\_\_\_\_

noir , RAL9005 <sup>1</sup> \_\_\_\_\_

cache-piton Noir profond \_\_\_\_\_

IP20 \_\_\_\_\_

699 lm \_\_\_\_\_

## LED

2700 K \_\_\_\_\_

CRI ≥ 90 \_\_\_\_\_

MacAdam initial ≤ 3 SDCM \_\_\_\_\_

R<sub>g</sub>: 99 , R<sub>f</sub>: 91 , R<sub>(1-15)</sub>: 89 \_\_\_\_\_

MR 0.53 \_\_\_\_\_

MDER 0.48 \_\_\_\_\_

## Optique

medium \_\_\_\_\_

angle de faisceau 25° \_\_\_\_\_

## Electrique

DALI-2 \_\_\_\_\_

système 12.0 W \_\_\_\_\_

insert 9.0 W \_\_\_\_\_

18 Vf \_\_\_\_\_

500 mA \_\_\_\_\_

CP2 220-240V \_\_\_\_\_

système 58 lm/W<sup>2</sup> \_\_\_\_\_

insert 78 lm/W<sup>3</sup> \_\_\_\_\_


## Physique

diamètre 26 mm \_\_\_\_\_

hauteur 500 mm \_\_\_\_\_

0.39 kg \_\_\_\_\_


## Répartition de la lumière



medium 25°

h (m)	E0° (lx)	ø (m)
1	2620	0.44
2	660	0.89
3	290	1.33
4	160	1.77
5	100	2.22

## Dessin de fabrication



<sup>1</sup> Code RAL

<sup>2</sup> incl. optical losses and the efficiency of the operating device (converter)

<sup>3</sup> incl. optical losses

## Notice de montage



## Calculateur d'éclairage

