

# TULA nano suspended

canopy surface

049-5710417F 005-2602197



Projet / Type \_\_\_\_\_

Notes \_\_\_\_\_

Quantité / Date \_\_\_\_\_



## Général

Plafond , Suspendu \_\_\_\_\_

blanc , RAL9016 <sup>1</sup> \_\_\_\_\_

cache-piton blanc signalisation \_\_\_\_\_

IP20 \_\_\_\_\_

674 lm \_\_\_\_\_

## LED

2700 K \_\_\_\_\_

CRI ≥ 90 \_\_\_\_\_

MacAdam initial ≤ 3 SDCM \_\_\_\_\_

R<sub>g</sub>: 99 , R<sub>f</sub>: 91 , R<sub>(1-15)</sub>: 89 \_\_\_\_\_

MR 0.53 \_\_\_\_\_

MDER 0.48 \_\_\_\_\_

## Optique

flood \_\_\_\_\_

angle de faisceau 30° \_\_\_\_\_

## Electrique

Casambi \_\_\_\_\_

système 12.0 W \_\_\_\_\_

insert 9.0 W \_\_\_\_\_

18 Vf \_\_\_\_\_

500 mA \_\_\_\_\_

CP2 220-240V \_\_\_\_\_

système 56 lm/W<sup>2</sup> \_\_\_\_\_

insert 75 lm/W<sup>3</sup> \_\_\_\_\_


## Physique

diamètre 26 mm \_\_\_\_\_

hauteur 500 mm \_\_\_\_\_

0.25 kg \_\_\_\_\_

## Répartition de la lumière



flood 30°

h (m)	E0° (lx)	ø (m)
1	1980	0.53
2	500	1.07
3	220	1.60
4	120	2.13
5	80	2.66

## Dessin de fabrication



<sup>1</sup> Code RAL  
<sup>2</sup> incl. optical losses and the efficiency of the operating device (converter)  
<sup>3</sup> incl. optical losses

## Notice de montage



## Calculateur d'éclairage

