

# TULA nano suspended

canopy surface

049-5510514M 005-2602138



Projet / Type \_\_\_\_\_

Notes \_\_\_\_\_

Quantité / Date \_\_\_\_\_



## Général

Plafond , Suspendu \_\_\_\_\_

chrome \_\_\_\_\_

cache-piton Noir profond \_\_\_\_\_

IP20 \_\_\_\_\_

744 lm \_\_\_\_\_

## LED

3000 K \_\_\_\_\_

CRI  $\geq$  90 \_\_\_\_\_

MacAdam initial  $\leq$  3 SDCM \_\_\_\_\_

R<sub>g</sub>: 100 , R<sub>f</sub>: 91 , R<sub>f(1-15)</sub>: 88 \_\_\_\_\_

MR 0.59 \_\_\_\_\_

MDER 0.53 \_\_\_\_\_

## Optique

medium \_\_\_\_\_

angle de faisceau 25° \_\_\_\_\_

## Electrique

DALI-2 \_\_\_\_\_

système 12.1 W \_\_\_\_\_

insert 9.1 W \_\_\_\_\_

18 Vf \_\_\_\_\_

500 mA \_\_\_\_\_

CP2 220-240V \_\_\_\_\_

système 61 lm/W<sup>1</sup> \_\_\_\_\_

insert 82 lm/W<sup>2</sup> \_\_\_\_\_


## Physique

diamètre 26 mm \_\_\_\_\_

hauteur 300 mm \_\_\_\_\_

0.29 kg \_\_\_\_\_


## Répartition de la lumière



medium 25°

h (m)	EO° (lx)	ø (m)
1	2790	0.44
2	700	0.89
3	310	1.33
4	170	1.77
5	110	2.22

## Dessin de fabrication



<sup>1</sup> incl. optical losses and the efficiency of the operating device (convertir)

<sup>2</sup> incl. optical losses

## Notice de montage



## Calculateur d'éclairage

