

TULA micro suspended

canopy trim

049-5515517M 005-3521017 002-90732



Projet / Type

Notes

Quantité / Date



220-240V

UGR ≤ 10

cd/m² ≤ 1500

CRI ≥ 90

X-PERT

Général

Plafond , Suspendu

blanc , RAL9016 ¹

cache-piton blanc signalisation

IP20

746 lm

LED

3000 K

CRI ≥ 90

L90 / 50000 h

MacAdam initial ≤ 3 SDCM

R_g: 100 , R_f: 90 , R_{f(1-15)}: 87

MR 0.59

MDER 0.54

Optique

medium

beam angle 25°

PstLM ≤ 1.0 ²

SVM ≤ 0.4 ²

Electrique

non DIM

11.3 W

insert 8.4 W

500 mA

CP2 220-240V

66 lm/W

Physique

diameter 47 mm

hauteur 300 mm

0.55 kg

Découpe


diameter 65 mm

min. ceiling thickness 2 mm

max. ceiling thickness 25 mm

recessed depth 70 mm



Répartition de la lumière



medium 25°

h (m)	E0° (lx)	ø (m)
1	3230	0.44
2	810	0.89
3	360	1.33
4	200	1.78
5	130	2.22

Dessin de fabrication



¹ Code RAL

² Valeur du produit contenant à pleine charge (non atténué)

Notice de montage



Calculateur d'éclairage

