

# TULA micro suspended

canopy trim

049-5515418F 005-3521018 002-90732



Projet / Type

Notes

Quantité / Date



220-240V

UGR  $\leq 16$

cd/m<sup>2</sup>  $\leq 1500$

CRI  $\geq 90$

X-PERT

## Général

Plafond , Suspendu

noir , RAL9005 <sup>1</sup>

cache-piton Noir profond

IP20

694 lm

## LED

2700 K

CRI  $\geq 90$

L90 / 50000 h

MacAdam initial  $\leq 3$  SDCM

R<sub>g</sub>: 99 , R<sub>r</sub>: 91 , R<sub>t(1-15)</sub>: 89

MR 0.54

MDER 0.49

## Optique

flood

beam angle 44°

PstLM  $\leq 1.0$  <sup>2</sup>

SVM  $\leq 0.4$  <sup>2</sup>

## Electrique

non DIM

11.3 W

insert 8.4 W

500 mA

CP2 220-240V

61 lm/W

## Physique

diameter 47 mm

hauteur 300 mm

0.54 kg

## Découpe

diameter 65 mm

min. ceiling thickness 2 mm


max. ceiling thickness 25 mm

recessed depth 70 mm

<sup>1</sup> Code RAL

<sup>2</sup> Valeur du produit contenant à pleine charge (non atténué)



## Répartition de la lumière



flood 44°

h (m)	E0° (lx)	ø (m)
1	1290	0.82
2	320	1.64
3	140	2.45
4	80	3.27
5	50	4.09

## Dessin de fabrication



## Notice de montage



## Calculateur d'éclairage

