

ARY cable suspended

canopy trim

049-5211617M 005-3521017 002-90732



Projet / Type

Notes

Quantité / Date



220-240V

UGR

cd/m²

CRI

X-PERT

Général

Plafond , Suspendu

blanc , RAL9016 ¹

cache-piton blanc signalisation

IP20

739 lm

LED

4000 K

CRI ≥ 90

L90 / 50000 h

MacAdam initial ≤ 3 SDCM

R_g: 99 , R_f: 89 , R_{t(1-15)}: 87

MR 0.81

MDER 0.73

Optique

medium

beam angle 25°

PstLM ≤ 1.0 ²

SVM ≤ 0.4 ²

Electrique

non DIM

11.2 W

CP2 220-240V

66 lm/W

Physique

suspension de 2000 mm avec crochet

diameter 47 mm

hauteur 110 mm

0.58 kg

Découpe

diameter 65 mm

min. ceiling thickness 2 mm


max. ceiling thickness 25 mm

recessed depth 70 mm

¹ Code RAL

² Valeur du produit contenant à pleine charge (non atténué)

Répartition de la lumière



medium 25°

h (m)	E0° (lx)	ø (m)
1	3200	0.44
2	800	0.89
3	360	1.33
4	200	1.78
5	130	2.22

Dessin de fabrication



Notice de montage



Calculateur d'éclairage

