

# ARY adjustable rod suspended canopy surface


049-523151XF 005-2602197



Projet / Type \_\_\_\_\_

Notes \_\_\_\_\_

Quantité / Date \_\_\_\_\_



**Général**

Plafond , Suspendu \_\_\_\_\_

inclinaison max 90° \_\_\_\_\_

rotation 265° \_\_\_\_\_

couleurs spéciales \_\_\_\_\_

cache-piton blanc signalisation \_\_\_\_\_

IP20 \_\_\_\_\_

791 lm \_\_\_\_\_

**LED**

3000 K \_\_\_\_\_

CRI ≥ 90 \_\_\_\_\_

L90 / 50000 h \_\_\_\_\_

MacAdam initial ≤ 3 SDCM \_\_\_\_\_

R<sub>g</sub>: 100 , R<sub>f</sub>: 90 , R<sub>f(1-15)</sub>: 87 \_\_\_\_\_

MR 0.59 \_\_\_\_\_

MDER 0.54 \_\_\_\_\_

**Optique**

flood \_\_\_\_\_

angle de faisceau 44° \_\_\_\_\_

**Electrique**

Casambi \_\_\_\_\_

11.2 W \_\_\_\_\_

CP2 220-240V \_\_\_\_\_

71 lm/W \_\_\_\_\_

**Physique**


barre de 1500 mm avec crochet \_\_\_\_\_

diamètre 47 mm \_\_\_\_\_

hauteur 110 mm \_\_\_\_\_


0.5 kg \_\_\_\_\_

## Répartition de la lumière



flood 44°		
h (m)	E0° (lx)	ø (m)
1	1470	0.82
2	370	1.64
3	160	2.45
4	90	3.27
5	60	4.09

## Dessin de fabrication



## Notice de montage



## Calculateur d'éclairage

