

# ARY adjustable rod suspended canopy surface

049-5131618F 005-2601118



Projet / Type \_\_\_\_\_

Notes \_\_\_\_\_

Quantité / Date \_\_\_\_\_



## Général

Plafond , Suspendu \_\_\_\_\_

inclinaison max 90° \_\_\_\_\_

rotation 265° \_\_\_\_\_

noir , RAL 9005 <sup>1</sup> \_\_\_\_\_

cache-piton noir profond \_\_\_\_\_

IP20 \_\_\_\_\_

791 lm \_\_\_\_\_

luminaire 94 lm/W<sup>2</sup> \_\_\_\_\_

## LED

4000 K \_\_\_\_\_

CRI ≥ 90 \_\_\_\_\_

L90 / 50000 h \_\_\_\_\_

MacAdam initial ≤ 3 SDCM \_\_\_\_\_

R<sub>g</sub>: 99 , R<sub>f</sub>: 89 , R<sub>t(1-15)</sub>: 87 \_\_\_\_\_

MR 0.81 \_\_\_\_\_

MDER 0.73 \_\_\_\_\_

## Optique

flood \_\_\_\_\_

angle de faisceau 44° \_\_\_\_\_

## Electrique

non DIM \_\_\_\_\_

220-240 V \_\_\_\_\_

système 11.2 W \_\_\_\_\_

luminaire 8.4 W \_\_\_\_\_

18 Vf \_\_\_\_\_

500 mA \_\_\_\_\_

CP2 \_\_\_\_\_

## Physique

barre 1500 mm \_\_\_\_\_


diamètre 47 mm \_\_\_\_\_

hauteur 110 mm \_\_\_\_\_

0.61 kg \_\_\_\_\_

<sup>1</sup> Code RAL  
<sup>2</sup> y compris la prise en compte des pertes optiques et des pertes de l'unité de contrôle interne


## Répartition de la lumière



flood 44°

h (m)	EO° (lx)	ø (m)
1	1470	0.82
2	370	1.64
3	160	2.45
4	90	3.27
5	60	4.09

## Dessin de fabrication



## Notice de montage



## Calculateur d'éclairage

