

SASSO 100 square adjustable

ceiling

048-33106371S



Projet / Type _____

Notes _____

Quantité / Date _____



220-240V

220-240V

X-PERT

X-PERT

Général

Plafond , Surface _____

inclinaison max 20° _____

blanc , RAL9016/black ¹ _____

Couleur intérieure noir _____

IP20 _____

1490 lm _____

LED

4000 K _____

CRI ≥ 90 _____

L80 / 50000 h _____

MacAdam initial ≤ 2 SDCM _____

R_g: 97 , R_f: 90 , R₍₁₋₁₅₎: 89 _____

MR 0.81 _____

MDER 0.74 _____

Optique

spot _____

angle de faisceau 19° _____

UGR < 13 , ≥65° <3000 cd/m² _____

P_{stLM} ≤ 1.0 ² _____

SVM ≤ 0.4 ² _____

Electrique

DALI-2 _____

20.2 W _____

CP1 220-240V _____

74 lm/W _____

1 DALI Addr. _____

Physique

longueur 100 mm _____

largeur 100 mm _____


hauteur 162 mm _____

1.1 kg _____


¹ Code RAL

² Valeur du produit contenant à pleine charge (non atténué)

Répartition de la lumière



Dessin de fabrication



Notice de montage



Calculateur d'éclairage

