

SASSO 100 square wallwasher/floor

trim 2 lamps

048-2750611W 048-279931G 002-90776



Projet / Type

Notes

Quantité / Date



Général

Plafond , Encastré

noir , RAL9005 ¹

Set de montage aluminium blanc

IP20

5440 lm

LED

4000 K

CRI ≥ 90

L80 / 50000 h

MacAdam initial ≤ 2 SDCM

R_g: 97 , R_f: 90 , R₍₁₋₁₅₎: 89

MR 0.81

MDER 0.74

Optique

wallwasher floor

PstLM ≤ 1.0 ²

SVM ≤ 0.4 ²

Electrique

DALI-2

55 W

insert 23.4 W

36 Vf

700 mA

nombre total d'inserts 47 W

CP2 220-240V

99 lm/W

insert 116 lm/W

Physique

bord

longueur 218 mm

largeur 118 mm

hauteur 96 mm

0.79 kg

Découpe

longueur 210 mm

largeur 112 mm

épaisseur min. du plafond 2 mm


épaisseur max. du plafond 25 mm

profondeur de l'encastrement 100 mm


¹ Code RAL

² Valeur du produit contenant à pleine charge (non atténué)

Répartition de la lumière



Dessin de fabrication



Notice de montage



Calculateur d'éclairage

