

SASSO 100 square wallwasher

trimless


048-2750417A 048-2797117 002-90779



Projet / Type

Notes

Quantité / Date



220-240V

X-PERT

CRI ≥ 90

X-PERT

Général

Plafond , Encastré

blanc , RAL9016 ¹

Set de montage blanc signalisation

IP20

1580 lm

LED

2700 K

CRI ≥ 90

L80 / 50000 h

MacAdam initial ≤ 3 SDCM

R_g: 97 , R_f: 91 , R_{f(1-15)}: 90

MR 0.53

MDER 0.48

Optique

wallwasher

PstLM ≤ 1.0 ²

SVM ≤ 0.4 ²

Electrique

DALI-2

20.3 W

insert 17.3 W

36 Vf

250 mA

CP2 220-240V

78 lm/W

insert 91 lm/W

Physique

sans bord

length 105 mm

width 105 mm

hauteur 96 mm

0.72 kg

Découpe

length 106 mm


width 106 mm

min. ceiling thickness 2 mm


max. ceiling thickness 25 mm

recessed depth 120 mm

Répartition de la lumière



Dessin de fabrication



¹ Code RAL

² Valeur du produit contenant à pleine charge (non atténué)

Notice de montage



Calculateur d'éclairage

