

SASSO 100 square downlight

trim

048-2710419M 048-2797317 002-90776



Projet / Type

Notes

Quantité / Date



Général

Plafond , Encastré

or , RAL260-M¹

Set de montage blanc signalisation

avant IP44 , arrière IP20

1860 lm

LED

2700 K

CRI ≥ 90

L80 / 50000 h

MacAdam initial ≤ 2 SDCM

R_g: 99 , R_r: 91 , R_{t(1-15)}: 89

MR 0.53

MDER 0.48

Optique

medium

angle de faisceau 33°x34°

UGR < 16 , $\geq 65^\circ$ < 3000 cd/m²

PstLM ≤ 1.0 ²

SVM ≤ 0.4 ²

Electrique

DALI-2

29.2 W

insert 24.8 W

36 Vf

700 mA

CP2 220-240V

64 lm/W

1 DALI Addr.

Physique

bord

longueur 118 mm

largeur 118 mm

hauteur 75 mm

0.53 kg

Découpe

longueur 112 mm

largeur 112 mm

épaisseur min. du plafond 2 mm

épaisseur max. du plafond 25 mm

profondeur de l'encastrement 80 mm

¹ Code RAL

² Valeur du produit contenant à pleine charge (non atténué)


Notice de montage



Calculateur d'éclairage



Répartition de la lumière



Dessin de fabrication

