

SASSO 100 square downlight

trimless

048-2710419M 048-2797117 002-90776



Projet / Type

Notes

Quantité / Date



Général

Plafond , Encastré

or , RAL260-M¹

Set de montage blanc signalisation

avant IP44 , arrière IP20

1860 lm

LED

2700 K

CRI ≥ 90

L80 / 50000 h

MacAdam initial ≤ 2 SDCM

R_g: 99 , R_r: 91 , R_{t(1-15)}: 89

MR 0.53

MDER 0.48

Optique

medium

angle de faisceau 33°x34°

UGR < 16 , $\geq 65^\circ$ < 3000 cd/m²

PstLM ≤ 1.0 ²

SVM ≤ 0.4 ²

Electrique

DALI-2

29.2 W

insert 24.8 W

36 Vf

700 mA

CP2 220-240V

64 lm/W

1 DALI Addr.

Physique

sans bord

longueur 105 mm

largeur 105 mm

hauteur 75 mm

0.51 kg

Découpe

longueur 106 mm

largeur 106 mm

épaisseur min. du plafond 12.5 mm


épaisseur max. du plafond 25 mm

profondeur de l'encastrement 80 mm



¹ Code RAL

² Valeur du produit contenant à pleine charge (non atténué)

Répartition de la lumière



Dessin de fabrication



Notice de montage



Calculateur d'éclairage

