

SASSO 100 round downlight

trim

048-2700611F 048-2796317 002-90779



Projet / Type

Notes

Quantité / Date



Général

Plafond , Encastré
noir , RAL9005 ¹
Set de montage blanc signalisation
avant IP44 , arrière IP20
1670 lm

LED

4000 K
CRI ≥ 90
L80 / 50000 h
MacAdam initial ≤ 2 SDCM
R_g: 97 , R_f: 90 , R_{t(1-15)}: 89
MR 0.81
MDER 0.74


Optique

flood
beam angle 45°
UGR < 16 , ≥65° <1500 cd/m²
PstLM ≤ 1.0 ²
SVM ≤ 0.4 ²


Electrique

DALI-2
20.2 W
insert 17.2 W
36 Vf
500 mA
CP2 220-240V
83 lm/W
insert 97 lm/W
1 DALI Addr.

Répartition de la lumière



Dessin de fabrication



Physique

bord
diamètre 118 mm
hauteur 75 mm
0.5 kg

Découpe

diamètre 108 mm
min. ceiling thickness 2 mm
max. ceiling thickness 25 mm
recessed depth 80 mm

¹ Code RAL
² Valeur du produit contenant à pleine charge (non atténué)

Notice de montage



Calculateur d'éclairage

