

# SASSO 100 round downlight

trim

048-2700511S 048-2796317 002-90776



Projet / Type

Notes

Quantité / Date



## Général

Plafond , Encastré  
noir , RAL9005 <sup>1</sup>  
Set de montage blanc signalisation  
avant IP44 , arrière IP20  
1830 lm

## LED

3000 K  
CRI ≥ 90  
L80 / 50000 h  
MacAdam initial ≤ 2 SDCM  
R<sub>g</sub>: 100 , R<sub>f</sub>: 91 , R<sub>(1-15)</sub>: 88  
MR 0.59  
MDER 0.53


## Optique

spot  
beam angle 19°  
UGR < 13 , ≥ 65° < 3000 cd/m²  
PstLM ≤ 1.0 <sup>2</sup>  
SVM ≤ 0.4 <sup>2</sup>


## Electrique

DALI-2  
29.2 W  
insert 24.8 W  
36 Vf  
700 mA  
CP2 220-240V  
63 lm/W  
insert 74 lm/W  
1 DALI Addr.

## Répartition de la lumière



## Dessin de fabrication



## Physique

bord  
diameter 118 mm  
hauteur 75 mm  
0.49 kg

## Découpe

diameter 108 mm  
min. ceiling thickness 2 mm  
max. ceiling thickness 25 mm  
recessed depth 80 mm

<sup>1</sup> Code RAL  
<sup>2</sup> Valeur du produit contenant à pleine charge (non atténué)

## Notice de montage



## Calculateur d'éclairage

