

SASSO 60 round wallwasher/floor

trim

048-2641511W 048-2696317 002-90771



Projet / Type
Notes
Quantité / Date



220-240V
360°
X-PERT
CRI ≥ 90
X-PERT

Général

Plafond , Encastré
rotation 360°
noir , RAL9005 ¹
Set de montage blanc signalisation
IP20
789 lm

LED

3000 K
CRI ≥ 90
L80 / 50000 h
MacAdam initial ≤ 3 SDCM
R _g : 97 , R _f : 91 , R ₍₁₋₁₅₎ : 89
MR 0.6
MDER 0.54

Optique

wallwasher floor
PstLM ≤ 1.0 ²
SVM ≤ 0.4 ²

Electrique

non DIM
9.7 W
insert 8.3 W
27 Vf
300 mA
CP2 220-240V
81 lm/W
insert 96 lm/W

Physique


bord
diameter 80 mm
hauteur 48 mm
0.21 kg

Découpe

diameter 73 mm
min. ceiling thickness 2 mm
max. ceiling thickness 25 mm
recessed depth 60 mm

¹ Code RAL
² Valeur du produit contenant à pleine charge (non atténué)

Répartition de la lumière



Dessin de fabrication



Notice de montage



Calculateur d'éclairage

