

SASSO 60 round wallwasher

trim

048-2641414A 048-269631G 002-90762



Projet / Type _____

Notes _____

Quantité / Date _____



Général

Plafond , Encastré _____

rotation 360° _____

argent mat _____

Set de montage aluminium blanc _____

IP20 _____

710 lm _____

LED

2700 K _____

CRI ≥ 90 _____

L80 / 50000 h _____

MacAdam initial ≤ 3 SDCM _____

R_g: 97 , R_f: 91 , R₍₁₋₁₅₎: 90 _____

MR 0.53 _____

MDER 0.48 _____

Optique

wallwasher _____

PstLM ≤ 1.0 ¹ _____

SVM ≤ 0.4 ¹ _____

Electrique

DALI-2 _____

9.7 W _____

insert 8.3 W _____

27 Vf _____

300 mA _____

CP2 220-240V _____

73 lm/W _____

insert 86 lm/W _____

1 DALI Addr. _____

Physique

bord _____

diameter 80 mm _____

hauteur 48 mm _____

0.27 kg _____

Découpe

diameter 73 mm _____


min. ceiling thickness 2 mm _____

max. ceiling thickness 25 mm _____

recessed depth 110 mm _____

¹ Valeur du produit contenant à pleine charge (non atténué)

Répartition de la lumière



Dessin de fabrication



Notice de montage



Calculateur d'éclairage

