

# SASSO 100 round wallwasher

trim

048-2740411A 048-2796318 002-90776



Projet / Type

Notes

Quantité / Date



220-240V

360°

X-PERT

CRI ≥ 90

X-PERT

### Général

Plafond , Encastré

rotation 360°

noir , RAL9005 <sup>1</sup>

Set de montage Noir profond

IP20

1880 lm

### LED

2700 K

CRI ≥ 90

L70 / 50000 h

MacAdam initial ≤ 3 SDCM

R<sub>g</sub>: 97 , R<sub>f</sub>: 91 , R<sub>(1-15)</sub>: 90

MR 0.53

MDER 0.48

### Optique

wallwasher

PstLM ≤ 1.0 <sup>2</sup>

SVM ≤ 0.4 <sup>2</sup>

### Electrique

DALI-2

29.4 W

insert 25.0 W

36 Vf

350 mA

CP2 220-240V

64 lm/W

insert 75 lm/W

### Physique

bord

diameter 118 mm

hauteur 96 mm

0.69 kg

### Découpe


diameter 108 mm

min. ceiling thickness 2 mm

max. ceiling thickness 25 mm

recessed depth 120 mm

### Répartition de la lumière



### Dessin de fabrication



<sup>1</sup> Code RAL  
<sup>2</sup> Valeur du produit contenant à pleine charge (non atténué)

### Notice de montage



### Calculateur d'éclairage

