

# SASSO 60 round wallwasher/floor

trimless exposed concrete

048-2641619W 048-2695210 002-90762



Projet / Type

Notes

Quantité / Date



## Général

Plafond , Encastré

rotation 360°

or , RAL260-M <sup>1</sup>

Set de montage aluminium blanc

IP20

798 lm

## LED

4000 K

CRI ≥ 90

L80 / 50000 h

MacAdam initial ≤ 3 SDCM

R<sub>g</sub>: 94 , R<sub>f</sub>: 87 , R<sub>(1-15)</sub>: 86

MR 0.8

MDER 0.72

## Optique

wallwasher floor

PstLM ≤ 1.0 <sup>2</sup>

SVM ≤ 0.4 <sup>2</sup>

## Electrique

DALI-2

9.7 W

insert 8.3 W

27 Vf

300 mA

CP2 220-240V

82 lm/W

insert 97 lm/W

1 DALI Addr.

## Physique

trimless for exposed concrete ceiling

length 230 mm

width 230 mm

hauteur 162 mm

2.41 kg

## Découpe

recessed depth 120 mm

<sup>1</sup> Code RAL

<sup>2</sup> Valeur du produit contenant à pleine charge (non atténué)


## Notice de montage



## Calculateur d'éclairage



## Répartition de la lumière



## Dessin de fabrication

