

# SASSO 60 round wallwasher/floor

trimless exposed concrete  
048-2641417W 048-2695210 002-90762



Projet / Type

Notes

Quantité / Date



Général

Plafond , Encastré

rotation 360°

blanc , RAL9016 <sup>1</sup>

Set de montage aluminium blanc

IP20

748 lm

LED

2700 K

CRI ≥ 90

L80 / 50000 h

MacAdam initial ≤ 3 SDCM

R<sub>g</sub>: 97 , R<sub>f</sub>: 91 , R<sub>(1-15)</sub>: 90

MR 0.53

MDER 0.48

Optique

wallwasher floor

PstLM ≤ 1.0 <sup>2</sup>

SVM ≤ 0.4 <sup>2</sup>

Electrique

DALI-2

9.7 W

insert 8.3 W

27 Vf

300 mA

CP2 220-240V

77 lm/W

insert 91 lm/W

1 DALI Addr.

Physique

trimless for exposed concrete ceiling

length 230 mm

width 230 mm


hauteur 162 mm

2.41 kg


Découpe

recessed depth 120 mm

## Répartition de la lumière



## Dessin de fabrication



<sup>1</sup> Code RAL  
<sup>2</sup> Valeur du produit contenant à pleine charge (non atténué)

## Notice de montage



## Calculateur d'éclairage

