

INO 1200 circle acoustic

luminaire mounted
034-370411W



Projet / Type

Notes

Quantité / Date



Élément acoustique en feutre PET de haute qualité, autoportant, avec des caractéristiques d'absorption acoustique, composé à 50% de PET recyclé ; forme ronde ; esthétique et haptique de la surface de haute qualité, blanc ; déviations de couleurs possibles ; pour montage sur suspensions par câble INO circle suspended, au-dessus du luminaire ; montage postérieur possible ;

Général

Luminaire / Rail , Monté

blanc

Physique

diamètre 1050 mm

hauteur 9 mm

0.84 kg

Acoustics

Alpha w (α_w) up to 0.6 ¹

SAC (sound absorption class) up to C ¹

NRC up to 0.55 ¹

SAA up to 0.57 ¹

¹ Alpha w, SAC, NRC, SAA refer to the best result of the entire product family

Notice de montage



INO 1200 circle acoustic

luminaire mounted
034-370411W



Projet / Type

Notes

Quantité / Date

product-datasheet.soundabsorption

125 HZ	250 HZ	500 HZ	1000 HZ	2000 HZ	4000 HZ
0.63	0.57	0.83	0.97	1.2	1.37

product-datasheet.acoustic-coefficients-diagram

