

# INO 900 circle acoustic

luminaire mounted  
034-370311D



Projet / Type	
Notes	
Quantité / Date	



Élément acoustique en feutre PET de haute qualité, autoportant, avec des caractéristiques d'absorption acoustique, composé à 50% de PET recyclé ; forme ronde ; esthétique et haptique de la surface de haute qualité, marbre gris ; déviations de couleurs possibles ; pour montage sur suspensions par câble INO circle suspended, au-dessus du luminaire ; montage postérieur possible ;

## Général

Luminaire / Rail , Monté	
marbre gris	

## Physique

diamètre 794 mm	
hauteur 9 mm	
0.94 kg	

## Acoustics

Alpha w ( $\alpha_w$ ) up to 0.6 <sup>1</sup>	
SAC (sound absorption class) up to C <sup>1</sup>	
NRC up to 0.55 <sup>1</sup>	
SAA up to 0.57 <sup>1</sup>	

<sup>1</sup> Alpha w, SAC, NRC, SAA refer to the best result of the entire product family

## Notice de montage



# INO 900 circle acoustic

luminaire mounted  
034-370311D



Projet / Type

Notes

Quantité / Date

## product-datasheet.soundabsorption

125 HZ	250 HZ	500 HZ	1000 HZ	2000 HZ	4000 HZ
0.3	0.27	0.47	0.53	0.63	0.8

## product-datasheet.acoustic-coefficients-diagram

