



SASSO 60/100 square

ceiling

EN Square ceiling mounted spotlight made of aluminium, available in 2 sizes; light inset lacquered; housing powder coated; luminaire housing can be attached to mounting plate without tools by interlock; choice of adjustable / fixed symmetric or asymmetric radiation characteristic; variants with sym. radiation characteristic: precise due to high quality lens system; variants with asym. radiation characteristic: high-quality reflector with micro-faceted, aluminum-vaporised surface; COB (Chip on Board) technology for maximum efficiency (ADJUSTABLE and DOWNLIGHT); no multiple shadows; efficient LEDs with very good colour rendering; luminaire for through wiring; converter integrated into spotlight head


FR Spot de plafond carré en aluminium, disponible dans 2 tailles ; insert d'éclairage peint ; boîtier thermolaqué ; corps de luminaire pouvant être monté sans outils sur la plaque de montage grâce à un système de verrouillage ; au choix de l'orientation / symétrique Fixe ou asymétrique caractéristique du flux ; variantes à rayonnement sym. : précises grâce à l'optique à lentille ; variantes à rayonnement asym. : réflecteur avec surface à microfacettes et revêtement alum. atténuant ; Technologie COB (Chip on Board) pour efficacité maximale (ADJUSTABLE et DOWNLIGHT) ; pas d'ombres multiples ; LED économes en énergie à restitution de couleur élevée ; luminaire pour câblage continu ; convertisseur intégré à la tête de spot

Quickinfo

2700 K, 3000 K, 4000 K
 CRI ≥ 90, 2 SDCM
 SASSO 60 up to 94lm/W
 SASSO 100 up to 101lm/W
 L80 @ 50 000h
 non DIM, DALI-2

Types

ceiling



Housing colours



Inset colours




Light distributions

SASSO 60




SASSO 100



wallwasher and
ww floor inset



glare control
(UGR ≤ 16)



easy mounting;
no visible screws



CWD
1800–3000K



CRI ≥ 95
2 SDCM

Order options

COLOUR TEMPERATURE

2700 K	4
3000 K	5
4000 K	6

CONTROL

non DIM	1
DALI-2	3

HOUSING COLOUR

<input type="radio"/> traffic white RAL 9016	7
<input checked="" type="radio"/> jet black RAL 9005	1

INSET COLOUR

<input type="radio"/> traffic white RAL 9016 (UGR \leq 22)	7
<input type="radio"/> matt silver (UGR \leq 19)	4
<input checked="" type="radio"/> jet black RAL 9005 (UGR \leq 16)	1
<input type="radio"/> gold dust RAL 260-M (UGR \leq 19)	9

BEAM ANGLE SASSO 60

spot 11°	S
medium 21°	M
flood 42°	F
wide flood 54°	W

BEAM ANGLE SASSO 100

spot 19°	S
medium 34°	M
flood 45°	F
wide flood 65°	W

Options on request

COLOUR RENDERING INDEX

CRI \geq 95, 2 SDCM

COLOUR TEMPERATURE

CWD 1800–3000 K

not for WW & WWF version

BEAM ANGLE SASSO 100

super wide flood 70°



SASSO 60 square ceiling



DOWNLIGHT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
11.6 W	2700 K	857 lm	0 4 8 - 3 0 1 0 :: ◆ ◆ ◆ ▲
	3000 K	927 lm	
	4000 K	996 lm	




WALLWASHER

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
11.4 W	2700 K	617 lm	0 4 8 - 3 6 1 0 :: ◆ ◆ ◆ ▲
	3000 K	617 lm	
	4000 K	726 lm	

WALLWASHER/FLOOR

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
11.4 W	2700 K	633 lm	0 4 8 - 3 6 1 0 :: ◆ ◆ ◆ W
	3000 K	633 lm	
	4000 K	746 lm	



SASSO 100 square ceiling



ADJUSTABLE

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
20.2 W	2700 K	1700 lm	0 4 8 - 3 3 1 0 :: ◆ ◆ ◆ ▲
	3000 K	1840 lm	
	4000 K	1980 lm	