

SASSO 100 round downlight

trim

048-2700617X 048-279631G 002-90774



Projet / Type

Notes

Quantité / Date



↑ IP20
↓ IP44

220-240V

X-PERT

CRI
≥ 90

X-PERT

Général

Plafond , Encastré

blanc , RAL9016 ¹

Set de montage aluminium blanc

avant IP44 , arrière IP20

2170 lm

LED

4000 K

CRI ≥ 90

L80 / 50000 h

MacAdam initial ≤ 2 SDCM

R_g: 97 , R_f: 90 , R_{t(1-15)}: 89

MR 0.81

MDER 0.74

Optique

super wide flood

beam angle 69°

PstLM ≤ 1.0 ²

SVM ≤ 0.4 ²

Electrique

non DIM

29.2 W

insert 24.8 W

36 Vf

700 mA

CP2 220-240V

74 lm/W

insert 87 lm/W

Physique

bord

diameter 118 mm

hauteur 75 mm

0.44 kg

Découpe

diameter 108 mm

min. ceiling thickness 2 mm


max. ceiling thickness 25 mm

recessed depth 80 mm


¹ Code RAL

² Valeur du produit contenant à pleine charge (non atténué)

Répartition de la lumière



Dessin de fabrication



Notice de montage



Calculateur d'éclairage

