

SASSO 100 round downlight

trimless

048-2700617X 048-2796117 002-90776



Projet / Type _____

Notes _____

Quantité / Date _____



↑ IP20
↓ IP44

220-240V

X-PERT

CRI
≥ 90

DALI
1ADDR.

X-PERT

Général

Plafond , Encastré
blanc , RAL9016 ¹
Set de montage blanc signalisation
avant IP44 , arrière IP20
2170 lm

LED

4000 K
CRI ≥ 90
L80 / 50000 h
MacAdam initial ≤ 2 SDCM
R_g: 97 , R_f: 90 , R_{t(1-15)}: 89
MR 0.81
MDER 0.74

Optique

super wide flood
beam angle 69°
PstLM ≤ 1.0 ²
SVM ≤ 0.4 ²

Electrique

DALI-2
29.2 W
insert 24.8 W
36 Vf
700 mA
CP2 220-240V
74 lm/W
insert 87 lm/W
1 DALI Addr.


Physique

sans bord
diameter 105 mm
hauteur 75 mm
0.55 kg


Découpe

diameter 106 mm
min. ceiling thickness 12.5 mm
max. ceiling thickness 25 mm
recessed depth 80 mm

Répartition de la lumière



Dessin de fabrication



¹ Code RAL

² Valeur du produit contenant à pleine charge (non atténué)

Notice de montage



Calculateur d'éclairage

