

# MINO 60 high lumen

surface

046-41M5038H



Projet / Type
Notes
Quantité / Date



220-240V
X-PERT
CRI ≥ 90
1ADDR
X-PERT

## Général

Plafond , Surface
noir , RAL9005 <sup>1</sup>
2020 lm/m
IP20
2980 lm

## LED

3000 K
CRI ≥ 90
L90 / 50000 h
sécurité photobio. RG 0 - aucun risque
MacAdam initial ≤ 3 SDCM
R <sub>g</sub> : 99 , R <sub>f</sub> : 91 , R <sub>(1-15)</sub> : 89
MR 0.61
MDER 0.55

## Optique

High Performance Opal
opal (lambertsch)
PstLM ≤ 1.0 <sup>2</sup>
SVM ≤ 0.4 <sup>2</sup>


## Electrique

DALI-2
29.1 W
CP1 220-240V
102 lm/W
1 DALI Addr.
20 W/m

## Physique

length 1480 mm
width 60 mm
hauteur 80 mm
3.8 kg

## Répartition de la lumière



## Dessin de fabrication



<sup>1</sup> Code RAL  
<sup>2</sup> Valeur du produit contenant à pleine charge (non atténué)

## Notice de montage



## Calculateur d'éclairage

