



Projet / Type \_\_\_\_\_

Notes \_\_\_\_\_

Quantité / Date \_\_\_\_\_



Général

Mur , Surface \_\_\_\_\_

aluminium anodisé \_\_\_\_\_

blanc pur \_\_\_\_\_

IP20 \_\_\_\_\_

7160 lm \_\_\_\_\_

LED

3000 K \_\_\_\_\_

CRI ≥ 90 \_\_\_\_\_

L80 / 50000 h \_\_\_\_\_

sécurité photobio. RG 0 - aucun risque \_\_\_\_\_

MacAdam initial ≤ 3 SDCM \_\_\_\_\_

R<sub>g</sub>: 99 , R<sub>f</sub>: 91 , R<sub>(1-15)</sub>: 89 \_\_\_\_\_

MR 0.61 \_\_\_\_\_

MDER 0.55 \_\_\_\_\_

Optique

Linear Prismatic \_\_\_\_\_

PstLM ≤ 1.0 <sup>1</sup> \_\_\_\_\_

SVM ≤ 0.4 <sup>1</sup> \_\_\_\_\_

Electrique

DALI-2 \_\_\_\_\_

65 W \_\_\_\_\_

CP1 220-240V \_\_\_\_\_

110 lm/W \_\_\_\_\_

1 DALI Addr. \_\_\_\_\_

Physique

longueur 1007 mm \_\_\_\_\_


largeur 130 mm \_\_\_\_\_

hauteur 25 mm \_\_\_\_\_



1.7 kg \_\_\_\_\_

<sup>1</sup> Valeur du produit contenant à pleine charge (non atténué)

Répartition de la lumière



Dessin de fabrication



Notice de montage

