

# MOVE IN 45 round

trimless

063-8121418V 063-8812117 002-90726



Projet / Type

Notes

Quantité / Date



220-240V

X-PERT

UGR  $\leq 10$

CRI  $\geq 90$

X-PERT

**Général**

Plafond , Demi-encastré

noir , RAL9005 <sup>1</sup>

IP20

400 lm

**LED**

2700 K

CRI  $\geq 90$

L85 / 50000 h

MacAdam initial  $\leq 3$  SDCM

R<sub>g</sub>: 99 , R<sub>f</sub>: 91 , R<sub>(1-15)</sub>: 89

MR 0.54

MDER 0.49

**Optique**

super spot

beam angle 8°

PstLM  $\leq 1.0$  <sup>2</sup>

SVM  $\leq 0.4$  <sup>2</sup>

**Electrique**

non DIM

9.2 W

insert 6.9 W

11 Vf

600 mA

CP2 220-240V

43 lm/W

**Physique**

sans bord

diameter 75 mm

hauteur 106 mm

0.59 kg

**Découpe**

diameter 65 mm

min. ceiling thickness 9 mm

max. ceiling thickness 25 mm

recessed depth 200 mm

## Répartition de la lumière



super spot 8°

h (m)	E0° (lx)	ø (m)
1	14000	0.14
2	3500	0.28
3	1600	0.41
4	900	0.55
5	600	0.69

## Dessin de fabrication



<sup>1</sup> Code RAL

<sup>2</sup> Valeur du produit contenant à pleine charge (non atténué)

