

# TILA 16 adjustable

MOVE IT 10

030-6500435F



Projet / Type \_\_\_\_\_

Notes \_\_\_\_\_

Quantité / Date \_\_\_\_\_



## Général

Plafond / mur , Rail \_\_\_\_\_

inclinaison max 135° \_\_\_\_\_

rotation 365° \_\_\_\_\_

gun metal \_\_\_\_\_

IP20 \_\_\_\_\_

205 lm \_\_\_\_\_

insert optique 77 lm/W<sup>1</sup> \_\_\_\_\_

## LED

2700 K \_\_\_\_\_

CRI ≥ 90 \_\_\_\_\_

L85 / 50000 h \_\_\_\_\_

MacAdam initial ≤ 3 SDCM \_\_\_\_\_

R<sub>g</sub>: 99 , R<sub>r</sub>: 91 , R<sub>t(1-15)</sub>: 89 \_\_\_\_\_

MR 0.54 \_\_\_\_\_

MDER 0.49 \_\_\_\_\_

## Optique

flood \_\_\_\_\_

angle de faisceau 31° \_\_\_\_\_

PstLM ≤ 1.0<sup>2</sup> \_\_\_\_\_

SVM ≤ 0.4<sup>2</sup> \_\_\_\_\_

## Electrique

DALI-2 \_\_\_\_\_

48 V \_\_\_\_\_

luminaire 3.3 W \_\_\_\_\_

insert optique 2.6 W \_\_\_\_\_

CP3 \_\_\_\_\_


1 DALI Addr. \_\_\_\_\_

## Physique

diamètre 16 mm \_\_\_\_\_

hauteur 80 mm \_\_\_\_\_


## Répartition de la lumière



flood 31°

h (m)	EO° (lx)	ø (m)
1	681	0.56
2	170	1.12
3	76	1.67
4	43	2.23
5	27	2.79

## Dessin de fabrication



<sup>1</sup> INSERT OPTIQUE: y compris la prise en compte des pertes optiques.

<sup>2</sup> Valeur du produit contenant à pleine charge (non atténué)

## Notice de montage

