

MOVE IN 45 flex round

trimless

063-8221518F 063-8812117 002-90728



Projet / Type
Notes
Quantité / Date



Général

Plafond , Demi-encastré
inclinaison max 90°
rotation 360°
noir , RAL9005 ¹
IP20
1310 lm

LED

3000 K
CRI ≥ 90
L80 / 50000 h
MacAdam initial ≤ 2 SDCM
R _g : 100 , R _f : 91 , R _{1-15} : 88
MR 0.59
MDER 0.53

Optique

flood
beam angle 36°
PstLM ≤ 1.0 ²
SVM ≤ 0.4 ²

Electrique

DALI-2
15.9 W
insert 13.5 W
36 V _f
400 mA
CP2 220-240V
82 lm/W
1 DALI Addr.

Physique


sans bord
diameter 75 mm
hauteur 106 mm
0.36 kg

Découpe

diameter 65 mm
min. ceiling thickness 9 mm
max. ceiling thickness 25 mm
recessed depth 195 mm

¹ Code RAL
² Valeur du produit contenant à pleine charge (non atténué)



Répartition de la lumière



flood 36°

h (m)	E0° (lx)	ø (m)
1	3900	0.65
2	980	1.29
3	430	1.94
4	240	2.59
5	160	3.23

Dessin de fabrication



Notice de montage



Calculateur d'éclairage

