

MOVE IN 45 round

trimless

063-8121518S 063-8812117 002-90720



Projet / Type _____

Notes _____

Quantité / Date _____



220-240V X-PERT CRI ≥ 90 DALI 1ADDR X-PERT

Général

Plafond , Demi-encastré

noir , RAL9005 ¹

IP20

1100 lm

LED

3000 K

CRI ≥ 90

L80 / 50000 h

MacAdam initial ≤ 2 SDCM

R_g: 100 , R_f: 91 , R_{f(1-5)}: 88

MR 0.59

MDER 0.53

Optique

spot

beam angle 12°

PstLM ≤ 1.0 ²

SVM ≤ 0.4 ²

Electrique

DALI-2

15.0 W

insert 12.8 W

37 Vf

350 mA

CP2 220-240V

73 lm/W

1 DALI Addr.

Physique

sans bord

diameter 75 mm

hauteur 106 mm

0.26 kg

Découpe


diameter 65 mm

min. ceiling thickness 9 mm

max. ceiling thickness 25 mm

recessed depth 195 mm

Répartition de la lumière



h (m)	E0° (lx)	ø (m)
1	13900	0.21
2	3500	0.42
3	1500	0.63
4	900	0.84
5	600	1.06

Dessin de fabrication



¹ Code RAL

² Valeur du produit contenant à pleine charge (non atténué)

Notice de montage

Calculateur d'éclairage

