

MOVE IN 45 round

trimless

063-8121518F 063-8812117 002-90728



Projet / Type

Notes

Quantité / Date



Général

Plafond , Demi-encastré

noir , RAL9005 ¹

IP20

1310 lm

LED

3000 K

CRI ≥ 90

L80 / 50000 h

MacAdam initial ≤ 2 SDCM

R_g: 100 , R_f: 91 , R_{f(1-5)}: 88

MR 0.59

MDER 0.53

Optique

flood

angle de faisceau 36°

PstLM ≤ 1.0 ²

SVM ≤ 0.4 ²

Electrique

DALI-2

15.9 W

insert 13.5 W

36 V_f

400 mA

CP2 220-240V

82 lm/W

insert 97 lm/W

1 DALI Addr.

Physique

sans bord

diamètre 75 mm

hauteur 106 mm

0.62 kg

Découpe


diamètre 65 mm

épaisseur min. du plafond 9 mm

épaisseur max. du plafond 25 mm

profondeur de l'encastrement 195 mm



Répartition de la lumière



flood 36°

h (m)	E0° (lx)	ø (m)
1	3900	0.65
2	980	1.29
3	430	1.94
4	240	2.59
5	160	3.23

Dessin de fabrication



¹ Code RAL

² Valeur du produit contenant à pleine charge (non atténué)

Notice de montage



Calculateur d'éclairage

