

# MOVE IN 45 round

trim

063-8121517S 063-8822118 002-90720



Projet / Type \_\_\_\_\_

Notes \_\_\_\_\_

Quantité / Date \_\_\_\_\_



220-240V X-PERT CRI ≥ 90 DALI 1ADDR X-PERT

## Général

Plafond , Demi-encastré  
blanc , RAL9016 <sup>1</sup>  
Set de montage Noir profond  
IP20  
1100 lm

## LED

3000 K  
CRI ≥ 90  
L80 / 50000 h  
MacAdam initial ≤ 2 SDCM  
R<sub>g</sub>: 100 , R<sub>f</sub>: 91 , R<sub>f(1-15)</sub>: 88  
MR 0.59  
MDER 0.53

## Optique

spot  
beam angle 12°  
PstLM ≤ 1.0 <sup>2</sup>  
SVM ≤ 0.4 <sup>2</sup>

## Electrique

DALI-2  
15.0 W  
insert 12.8 W  
37 Vf  
350 mA  
CP2 220-240V  
73 lm/W  
1 DALI Addr.

## Physique

bord  
diameter 77 mm  
hauteur 107 mm  
0.28 kg

## Découpe

diameter 65 mm  
min. ceiling thickness 2 mm  
max. ceiling thickness 25 mm  
recessed depth 195 mm

<sup>1</sup> Code RAL  
<sup>2</sup> Valeur du produit contenant à pleine charge (non atténué)

## Répartition de la lumière



spot 12°

h (m)	E0° (lx)	ø (m)
1	13900	0.21
2	3500	0.42
3	1500	0.63
4	900	0.84
5	600	1.06

## Dessin de fabrication



## Notice de montage



## Calculateur d'éclairage

