

MOVE IN 45 round

trim

063-8121517F 063-8822118 002-90728



Projet / Type
Notes
Quantité / Date



Général

Plafond , Demi-encasté
blanc , RAL9016 ¹
Set de montage Noir profond
IP20
1310 lm

LED

3000 K
CRI ≥ 90
L80 / 50000 h
MacAdam initial ≤ 2 SDCM
R _g : 100 , R _f : 91 , R _{f(1-15)} : 88
MR 0.59
MDER 0.53

Optique

flood
angle de faisceau 36°
PstLM ≤ 1.0 ²
SVM ≤ 0.4 ²

Electrique

DALI-2
15.9 W
insert 13.5 W
36 Vf
400 mA
CP2 220-240V
82 lm/W
1 DALI Addr.

Physique


bord
diamètre 77 mm
hauteur 107 mm
0.37 kg

Découpe

diamètre 65 mm
épaisseur min. du plafond 2 mm
épaisseur max. du plafond 25 mm
profondeur de l'encastrement 195 mm

¹ Code RAL
² Valeur du produit contenant à pleine charge (non atténué)


Répartition de la lumière



flood 36°

h (m)	E0° (lx)	ø (m)
1	3900	0.65
2	980	1.29
3	430	1.94
4	240	2.59
5	160	3.23

Dessin de fabrication



Notice de montage



Calculateur d'éclairage

