

# MOVE IN 45 round

trimless

063-8121418F 063-8812117 002-90728



Projet / Type \_\_\_\_\_

Notes \_\_\_\_\_

Quantité / Date \_\_\_\_\_



## Général

Plafond , Demi-encastré  
noir , RAL9005 <sup>1</sup>  
IP20  
1230 lm

## LED

2700 K  
CRI ≥ 90  
L80 / 50000 h  
MacAdam initial ≤ 2 SDCM  
R<sub>g</sub>: 99 , R<sub>f</sub>: 91 , R<sub>(1-15)</sub>: 89  
MR 0.53  
MDER 0.48

## Optique

flood  
beam angle 36°  
PstLM ≤ 1.0 <sup>2</sup>  
SVM ≤ 0.4 <sup>2</sup>

## Electrique

DALI-2  
15.9 W  
insert 13.5 W  
36 Vf  
400 mA  
CP2 220-240V  
77 lm/W  
1 DALI Addr.


## Physique

sans bord  
diameter 75 mm  
hauteur 106 mm  
0.36 kg

## Découpe

diameter 65 mm  
min. ceiling thickness 9 mm  
max. ceiling thickness 25 mm  
recessed depth 195 mm

## Répartition de la lumière



flood 36°

h (m)	E0° (lx)	ø (m)
1	3660	0.65
2	920	1.29
3	410	1.94
4	230	2.59
5	150	3.23

## Dessin de fabrication



<sup>1</sup> Code RAL  
<sup>2</sup> Valeur du produit contenant à pleine charge (non atténué)

## Notice de montage



## Calculateur d'éclairage

