

# MOVE IN 45 round

trimless

063-8121416S 063-8812117 002-90720



Projet / Type \_\_\_\_\_

Notes \_\_\_\_\_

Quantité / Date \_\_\_\_\_



220-240V X-PERT CRI ≥ 90 DALI 1ADDR X-PERT

## Général

Plafond , Demi-encastré  
aluminium brossé  
IP20  
1030 lm

## LED

2700 K  
CRI ≥ 90  
L80 / 50000 h  
MacAdam initial ≤ 2 SDCM  
R<sub>g</sub>: 99 , R<sub>f</sub>: 91 , R<sub>(1-15)</sub>: 89  
MR 0.53  
MDER 0.48

## Optique

spot  
beam angle 12°  
PstLM ≤ 1.0 <sup>1</sup>  
SVM ≤ 0.4 <sup>1</sup>

## Electrique

DALI-2  
14.9 W  
insert 12.7 W  
37 Vf  
350 mA  
CP2 220-240V  
69 lm/W  
1 DALI Addr.

## Physique


sans bord  
diameter 75 mm  
hauteur 106 mm  
0.46 kg

## Découpe

diameter 65 mm  
min. ceiling thickness 9 mm  
max. ceiling thickness 25 mm  
recessed depth 195 mm

<sup>1</sup> Valeur du produit contenant à pleine charge (non atténué)


## Répartition de la lumière



spot 12°

h (m)	E0° (lx)	ø (m)
1	13000	0.21
2	3300	0.42
3	1400	0.63
4	800	0.84
5	500	1.06

## Dessin de fabrication



## Notice de montage



## Calculateur d'éclairage

