

FRAME 60 high lumen

trim system

007-93M4137 006-16122H 035-01237



Projet / Type
Notes
Quantité / Date



220-240V
X-PERT
CRI ≥ 90
1ADDR
X-PERT

Général

Plafond , Encastré
blanc , RAL9016 ¹
2200 lm/m
IP20
2570 lm

LED

4000 K
CRI ≥ 90
L90 / 50000 h
sécurité photobio. RG 0 - aucun risque
MacAdam initial ≤ 3 SDCM
R _g : 99 , R _f : 92 , R ₍₁₋₁₅₎ : 90
MR 0.81
MDER 0.74

Optique

High Performance Opal
opal (lambertsch)
PstLM ≤ 1.0 ²
SVM ≤ 0.4 ²

Electrique

DALI-2
23.3 W
CP1 220-240V
110 lm/W
1 DALI Addr.
20 W/m

Physique


bord
length 1172 mm
width 77 mm
hauteur 78 mm
2.77 kg

Découpe

length 1188 mm
width 66 mm
min. ceiling thickness 8 mm
max. ceiling thickness 25 mm
recessed depth 108 mm

¹ Code RAL
² Valeur du produit contenant à pleine charge (non atténué)

Répartition de la lumière



Dessin de fabrication



Notice de montage



Calculateur d'éclairage

