

FRAME 60 high lumen

trim system

007-93M2537 006-16062Z 035-0063G



Projet / Type _____

Notes _____

Quantité / Date _____



220-240V

X-PERT

UGR ≤ 22

CRI ≥ 80

DALI-2 1ADDR.

X-PERT

Général

Plafond , Encastré

gris , RAL9006 ¹

2100 lm/m

IP20

1200 lm

LED

3000 K

CRI ≥ 80

L90 / 50000 h

sécurité photobio. RG 0 - aucun risque

MacAdam initial ≤ 3 SDCM

MR 0.56

MDER 0.51

Optique

Microprismatic

microprismatic

PstLM ≤ 1.0 ²

SVM ≤ 0.4 ²

Electrique

DALI-2

121 W

CP1 220-240V

99 lm/W

1 DALI Addr.

21 W/m

Physique

bord

length 572 mm

width 77 mm

hauteur 78 mm

1.6 kg

Découpe

length 588 mm


width 66 mm

min. ceiling thickness 8 mm


max. ceiling thickness 25 mm

recessed depth 108 mm

Répartition de la lumière



Dessin de fabrication



¹ Code RAL

² Valeur du produit contenant à pleine charge (non atténué)

Notice de montage



Calculateur d'éclairage

