

# FRAME 60 high lumen

trim system

007-9338D37 006-16232Z 035-0253G



Projet / Type
Notes
Quantité / Date



220-240V	X-PERT	TUNABLE WHITE	CRI ≥ 80	DALI-2 1ADDR.	X-PERT
----------	--------	---------------	----------	---------------	--------

## Général

Plafond , Encastré
gris , RAL9006 <sup>1</sup>
2230 lm/m
IP20
5230 lm

## LED

tunable white
2700 K - 6500 K
CRI ≥ 80
L90 / 50000 h
sécurité photobio. RG 0 - aucun risque
MacAdam initial ≤ 3 SDCM
MR 0.48
MDER 0.44

## Optique

Microprismatic
microprismatic
PstLM ≤ 1.0 <sup>2</sup>
SVM ≤ 0.4 <sup>2</sup>

## Electrique

DALI-2 DT8
49 W
CP1 220-240V
107 lm/W
1 DALI Addr.
21 W/m

## Physique


length 2344 mm
width 77 mm
hauteur 78 mm
5.8 kg

## Découpe


length 2360 mm
width 66 mm
min. ceiling thickness 8 mm
max. ceiling thickness 25 mm
recessed depth 108 mm

<sup>1</sup> Code RAL  
<sup>2</sup> Valeur du produit contenant à pleine charge (non atténué)

## Répartition de la lumière



## Dessin de fabrication



## Notice de montage



## Calculateur d'éclairage

