

# SETA 60 CONEX reflector direct / indirect plug / socket

suspended system

058-4124037B



Projet / Type

Notes

Quantité / Date



## Général

Plafond , Suspendu

blanc , RAL9010 <sup>1</sup>

chrome foncé

IP20

Indirect 2810 lm

direct 1630 lm

total 4440 lm

## LED

3000 K

CRI ≥ 90

L90 / 50000 h

MacAdam initial ≤ 3 SDCM

R<sub>g</sub>: 99 , R<sub>r</sub>: 91 , R<sub>t(1-15)</sub>: 89

MR 0.61

MDER 0.55

## Optique

Reflector

symmetric

UGR < 13 , ≥ 65° < 1500 cd/m<sup>2</sup>

PstLM ≤ 1.0 <sup>2</sup>

SVM ≤ 0.4 <sup>2</sup>

## Electrique

DALI-2

220-240 V

système 42 W

CP1

système 106 lm/W<sup>3</sup>

2 DALI Addr.

## Physique

longueur 1181 mm

largeur 60 mm

hauteur 60 mm



<sup>1</sup> Code RAL

<sup>2</sup> Valeur du produit contenant à pleine charge (non atténué)

<sup>3</sup> incl. optical losses and the efficiency of the operating device (converter)

## Répartition de la lumière

## Dessin de fabrication



## Notice de montage



## Calculateur d'éclairage

