



Projet / Type \_\_\_\_\_

Notes \_\_\_\_\_

Quantité / Date \_\_\_\_\_



**Général**

Éclairage de vitrine , Sur pied \_\_\_\_\_

rotation 360° \_\_\_\_\_

aluminium blanc , RAL9006 <sup>1</sup> \_\_\_\_\_

IP20 \_\_\_\_\_

Intérieur \_\_\_\_\_

1430 lm \_\_\_\_\_

**LED**

4000 K \_\_\_\_\_

CRI ≥ 95 \_\_\_\_\_

L80 / 50000 h \_\_\_\_\_

MacAdam initial ≤ 3 SDCM \_\_\_\_\_

R<sub>g</sub>: 99 , R<sub>f</sub>: 92 , R<sub>(1-15)</sub>: 89 \_\_\_\_\_

MR 0.76 \_\_\_\_\_

MDER 0.69 \_\_\_\_\_

**Optique**

medium \_\_\_\_\_

beam angle 32°x46° \_\_\_\_\_

**Electrique**

sans driver \_\_\_\_\_

24 V \_\_\_\_\_

24.3 W \_\_\_\_\_

CP3 24V \_\_\_\_\_

insert 88 lm/W \_\_\_\_\_

24 V \_\_\_\_\_

**Physique**


length 1200 mm \_\_\_\_\_

width 9 mm \_\_\_\_\_

hauteur 9 mm \_\_\_\_\_

<sup>1</sup> Code RAL

**Répartition de la lumière**



**Dessin de fabrication**



**Notice de montage**

