



Projet / Type \_\_\_\_\_

Notes \_\_\_\_\_

Quantité / Date \_\_\_\_\_



**Général**

Éclairage de vitrine , Sur pied \_\_\_\_\_

rotation 360° \_\_\_\_\_

aluminium blanc , RAL 9006 <sup>1</sup> \_\_\_\_\_

IP20 \_\_\_\_\_

Intérieur \_\_\_\_\_

634 lm \_\_\_\_\_

insert optique 78 lm/W<sup>2</sup> \_\_\_\_\_

**LED**

4000 K \_\_\_\_\_

CRI ≥ 95 \_\_\_\_\_

L80 / 50000 h \_\_\_\_\_

MacAdam initial ≤ 3 SDCM \_\_\_\_\_

R<sub>g</sub>: 99 , R<sub>r</sub>: 92 , R<sub>(1-15)</sub>: 89 \_\_\_\_\_

MR 0.76 \_\_\_\_\_

MDER 0.69 \_\_\_\_\_

**Optique**

asymmetric \_\_\_\_\_

**Electrique**

sans driver \_\_\_\_\_

24 V \_\_\_\_\_

luminaire 12.2 W \_\_\_\_\_

insert optique 8.2 W \_\_\_\_\_

CP3 \_\_\_\_\_

22 W/m \_\_\_\_\_

24 V \_\_\_\_\_

**Physique**


longueur 600 mm \_\_\_\_\_

largeur 9 mm \_\_\_\_\_

hauteur 9 mm \_\_\_\_\_

<sup>1</sup> Code RAL <sup>2</sup> y compris la prise en compte des pertes optiques.

**Répartition de la lumière**



**Dessin de fabrication**



**Notice de montage**

