



MITA circle

suspended


EN Ring shaped luminaire housing in die-cast aluminium; extremely slim design; surface powder coated; suspended; with height adjustable rod suspension (chrome), feed in rod; electronic operating unit installed in the canopy; optional: blind cover to cover the cut-out, held by magnet, available as an accessory; high gloss reflector with faceted design; HPO (High Performance Opal) cover for uniform illumination; either with direct or direct/indirect light distribution; energy-efficient LEDs with very good colour rendering

FR Corps de luminaire en forme d'anneau en fonte d'aluminium injectée; forme extrêmement élancée; surface thermolaquée; suspendu; avec suspension pouvant être raccourcie (chrome), conduit d'alimentation dans le tube de suspension; disp. électronique d'alimentation intégré au cache-piton; en option: cache, fixé par aimant dans l'encoche intérieure, disponible comme accessoire; réflecteur ultra-brillant avec optique à facettes; cache HPO (High Performance Opal) pour éclairage homogène; au choix avec caractéristique de rayonnement direct ou direct/indirect; LED économes en énergie à restitution de couleur élevée


Quickinfo

3000 K, 4000 K
 CRI ≥ 80, CRI ≥ 90, 3 SDCM
 UGR ≤ 19 / 65° ≤ 1500 cd/m²
 up to 160 lm/W
 L90 @ 50000h
 DALI-2
 reflector (UGR ≤ 19), opal


Types



Colours



Light distributions



up to 160 lm/W
 (high efficiency)



dark chrome reflector option



version with opal cover



magnetic blind cover



DIN EN 12464-1
 UGR ≤ 19

Order options

SUSPENSION

rod 1000 mm

COLOUR TEMPERATURE

3000 K (CRI \geq 90)	0
4000 K (CRI \geq 90)	1
3000 K (CRI \geq 80)	5
4000 K (CRI \geq 80)	6

CONTROL

DALI-2

MATERIAL COLOUR

<input type="radio"/> traffic white RAL 9016	7
<input checked="" type="radio"/> jet black RAL 9005	8

REFLECTOR COLOUR

<input checked="" type="checkbox"/> chrome	R
<input type="checkbox"/> dark chrome	B

LIGHT OPTIC COVER

reflector (UGR \leq 19)

opal

Options on request



SUSPENSION

rod 1000 mm white

rod 1000 mm black

COLOUR TEMPERATURE

tunable white 2700–6500 K



MITA circle 450 suspended



UGR
 ≤ 19

cd/m²
 ≤ 1500

DALI
1ADDR.

220-240V

X-PERT

X-PERT

REFLECTOR DIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
30 W	3000 K	4210 lm	074-76113
	4000 K	4790 lm	
40 W	3000 K	5470 lm	074-76213
	4000 K	6230 lm	

OPAL DIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
24.9 W	3000 K	2760 lm	074-76113
	4000 K	3140 lm	



UGR
 ≤ 19

cd/m²
 ≤ 1500

DALI
1ADDR.

220-240V

X-PERT

X-PERT

REFLECTOR DIRECT / INDIRECT POWER

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
60 W	3000 K	↓ 4170 / ± 3850 lm	074-76513
	4000 K	↓ 4750 / ± 4380 lm	

OPAL DIRECT / INDIRECT POWER

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
60 W	3000 K	↓ 3350 / ± 3850 lm	074-76513
	4000 K	↓ 3810 / ± 4380 lm	

Accessories

BLIND COVER

TYPE	ORDER CODE
MITA circle 450 suspended	074-891162