

# SASSO 60 round downlight

trim

048-2602911F 048-2696317 002-90742



Projet / Type

Notes

Quantité / Date



## Général

Plafond , Encastré  
rotation 360°  
noir , RAL9005 <sup>1</sup>  
Set de montage blanc signalisation  
avant IP44 , arrière IP20  
800 lm

## LED

2700 K  
CRI ≥ 90  
L80 / 50000 h  
MacAdam initial ≤ 2 SDCM  
R<sub>g</sub>: 97 , R<sub>f</sub>: 91 , R<sub>(1-15)</sub>: 87  
MR 0.52  
MDER 0.47


## Optique

flood  
beam angle 41°  
UGR < 16 , ≥65° <1500 cd/m<sup>2</sup>  
P<sub>stLM</sub> ≤ 1.0 <sup>2</sup>  
SVM ≤ 0.4 <sup>2</sup>

## Electrique

non DIM  
10.2 W  
insert 8.7 W  
36 Vf  
250 mA  
CP2 220-240V  
78 lm/W  
insert 92 lm/W

## Répartition de la lumière



## Dessin de fabrication



## Physique

bord  
diameter 80 mm  
hauteur 48 mm  
0.21 kg

## Découpe

diameter 73 mm  
min. ceiling thickness 2 mm  
max. ceiling thickness 25 mm  
recessed depth 60 mm

<sup>1</sup> Code RAL  
<sup>2</sup> Valeur du produit contenant à pleine charge (non atténué)

## Notice de montage



## Calculateur d'éclairage

