

SASSO 60 round downlight

trim

048-2602114S 048-2696318 002-90742



Projet / Type

Notes

Quantité / Date



↑ P20
↓ P44

220-240V

↺

☀
XPEST

UGR
≤ 16

cd/m²
≤ 1500

CRI
≥ 90

~
XPEST

Général

Plafond , Encastré

rotation 360°

argent mat

Set de montage Noir profond

avant IP44 , arrière IP20

614 lm

LED

4000 K

CRI ≥ 90

MacAdam initial ≤ 2 SDCM

R_g: 98 , R_f: 90 , R_{t(1-15)}: 88

MR 0.8

MDER 0.72

Optique

spot

beam angle 12°

UGR < 16 , ≥ 65° < 1500 cd/m²

PstLM ≤ 1.0 ¹

SVM ≤ 0.4 ¹

Electrique

non DIM

10.4 W

insert 8.8 W

36 Vf

250 mA

CP2 220-240V

59 lm/W

insert 69 lm/W

Physique

bord

diameter 80 mm

hauteur 48 mm

0.2 kg

Découpe

diameter 73 mm


min. ceiling thickness 2 mm

max. ceiling thickness 25 mm

recessed depth 60 mm

¹ Valeur du produit contenant à pleine charge (non atténué)

Répartition de la lumière



Dessin de fabrication



Notice de montage



Calculateur d'éclairage

