

# SASSO 60 round downlight

trimless exposed concrete

048-2602019M 048-2695210 002-90742



Projet / Type \_\_\_\_\_

Notes \_\_\_\_\_

Quantité / Date \_\_\_\_\_



## Général

Plafond , Encastré  
rotation 360°  
or , RAL260-M <sup>1</sup>  
Set de montage aluminium blanc  
avant IP44 , arrière IP20  
816 lm

## LED

3000 K  
CRI ≥ 90  
L80 / 50000 h  
MacAdam initial ≤ 2 SDCM  
R<sub>g</sub>: 99 , R<sub>f</sub>: 90 , R<sub>t(1-15)</sub>: 87  
MR 0.6  
MDER 0.54

## Optique

medium  
beam angle 21°  
UGR < 16 , ≥65° <3000 cd/m²  
P<sub>stLM</sub> ≤ 1.0 <sup>2</sup>  
SVM ≤ 0.4 <sup>2</sup>

## Electrique

non DIM  
10.2 W  
insert 8.7 W  
36 Vf  
250 mA  
CP2 220-240V  
80 lm/W  
insert 94 lm/W


## Physique

trimless for exposed concrete ceiling  
length 230 mm  
width 230 mm  
hauteur 162 mm  
2.35 kg



## Découpe

recessed depth 60 mm

## Répartition de la lumière



## Dessin de fabrication



<sup>1</sup> Code RAL

<sup>2</sup> Valeur du produit contenant à pleine charge (non atténué)

## Notice de montage



## Calculateur d'éclairage

