

SASSO 60 round downlight

trimless exposed concrete

048-2602014F 048-2695210 002-90742



Projet / Type

Notes

Quantité / Date



↑ IP20
↓ IP44

220-240V

360°

X-PEST

UGR
≤ 16

cd/m²
≤ 1500

CRI
≥ 90

X-PEST

Général

Plafond , Encastré

rotation 360°

argent mat

Set de montage aluminium blanc

avant IP44 , arrière IP20

921 lm

LED

3000 K

CRI ≥ 90

L80 / 50000 h

MacAdam initial ≤ 2 SDCM

R_g: 99 , R_f: 90 , R₍₁₋₁₅₎: 87

MR 0.6

MDER 0.54

Optique

flood

beam angle 42°

UGR < 16 , ≥ 65° < 1500 cd/m²

PstLM ≤ 1.0¹

SVM ≤ 0.4¹

Electrique

non DIM

10.2 W

insert 8.7 W

36 Vf

250 mA

CP2 220-240V

90 lm/W

insert 106 lm/W

Physique

trimless for exposed concrete ceiling

length 230 mm

width 230 mm

hauteur 162 mm


2.35 kg

Découpe



recessed depth 60 mm

¹ Valeur du produit contenant à pleine charge (non atténué)

Répartition de la lumière



Dessin de fabrication



Notice de montage



Calculateur d'éclairage

