

SASSO 60 round downlight

trimless exposed concrete

048-2602011F 048-2695210 002-90742



Projet / Type

Notes

Quantité / Date



↑ P20
↓ P44

220-240V

360°

UGR
≤16

cd/m²
≤1500

CRI
≥90

XPEST

Général

Plafond , Encastré

rotation 360°

noir , RAL9005 ¹

Set de montage aluminium blanc

avant IP44 , arrière IP20

830 lm

LED

3000 K

CRI ≥ 90

L80 / 50000 h

MacAdam initial ≤ 2 SDCM

R_g: 99 , R_f: 90 , R₍₁₋₁₅₎: 87

MR 0.6

MDER 0.54

Optique

flood

beam angle 41°

UGR < 16 , ≥65° <1500 cd/m²

PstLM ≤ 1.0 ²

SVM ≤ 0.4 ²

Electrique

non DIM

10.2 W

insert 8.7 W

36 Vf

250 mA

CP2 220-240V

81 lm/W

insert 95 lm/W

Physique

trimless for exposed concrete ceiling

length 230 mm

width 230 mm

hauteur 162 mm

2.35 kg


Découpe

recessed depth 60 mm

¹ Code RAL

² Valeur du produit contenant à pleine charge (non atténué)

Répartition de la lumière



Dessin de fabrication

