

SASSO 60 round downlight

trimless exposed concrete

048-2602117F 048-2695210 002-90746



Projet / Type

Notes

Quantité / Date



↑ P20

↓ P44

220-240V

↺

↻

☀

X-PEST

UGR

≤ 19

cd/m²

≤ 1500

CRI

≥ 90

~

X-PEST

Général

Plafond , Encastré

rotation 360°

blanc , RAL9016 ¹

Set de montage aluminium blanc

avant IP44 , arrière IP20

957 lm

LED

4000 K

CRI ≥ 90

L80 / 50000 h

MacAdam initial ≤ 2 SDCM

R_g: 98 , R_f: 90 , R₍₁₋₁₅₎: 88

MR 0.8

MDER 0.72

Optique

flood

beam angle 46°

UGR < 19 , ≥ 65° < 1500 cd/m²

PstLM ≤ 1.0 ²

SVM ≤ 0.4 ²

Electrique

DALI-2

10.0 W

insert 8.5 W

36 Vf

250 mA

CP2 220-240V

96 lm/W

insert 112 lm/W

Physique

trimless for exposed concrete ceiling

length 230 mm

width 230 mm

hauteur 162 mm

2.41 kg


Découpe

recessed depth 120 mm

¹ Code RAL

² Valeur du produit contenant à pleine charge (non atténué)

Répartition de la lumière



Dessin de fabrication

